

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
4 August 2005 (04.08.2005)

PCT

(10) International Publication Number
WO 2005/070782 A1

(51) International Patent Classification⁷: **B65D 51/18**

(21) International Application Number:
PCT/US2005/001665

(22) International Filing Date: 18 January 2005 (18.01.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/536,843 16 January 2004 (16.01.2004) US

(71) Applicant and

(72) Inventor: HEYN, William, M. [US/US]; 197 Bridle Path Lane, New Canaan, CT 06840 (US).

(74) Agent: HOLT, William, H.; Law Offices of William H. Holt, 12311 Harbor Drive, Woodbridge, VA 22192 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,

CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: OVERCAP FOR A CONTAINER



(57) Abstract: An overcap (30, 40, 60, 70, 80, 140) for a container (10, 50, 90) closed by a flexible end panel (18, 54, 98) is snapped or twisted or threaded onto the container to lie closely adjacent to the flexible end panel for reducing the possibility of the end panel being separated from the container incident to retorting or impact loading. The underside of the overcap may be provided with one or more depending annular rings or leg members (38, 46, 64, 66, 76, 146) to be placed closely adjacent to or in contact with the flexible end panel to preclude undesirable movement thereof.

WO 2005/070782 A1